



Peterbilt of St. Louis P616
2350 Sauget Industrial Parkway

Renegade RV
52216 S.R 15

Sauget, Illinois United States 62206
Phone:
Fax:
Email:

Bristol, Indiana United States 46507
Phone:
Fax:
Contact Email:
Prepared for:

Vehicle Summary

	Unit		Chassis	
Model:		Model 567	Fr Axle Load (lbs):	18000
Type:		Full Truck	Rr Axle Load (lbs)	40000
Description:		JR OWEN	G.C.W. (lbs):	66000
	Application		Road Conditions:	
Intended Serv.:		General Freight	Class A (Highway)	100
Commodity:		Other Commodity	Class B (Hwy/Mtn)	0
	Body		Class C (Off-Hwy)	0
Type:		Van	Class D (Off-Road)	0
Length (ft):		40	Maximum Grade:	6
Height (ft):		12.0	Wheelbase (in):	360
Max Laden Weight (lbs):		4000	Overhang (in):	60
	Trailer		Fr Axle to BOC (in):	90.1
No. of Trailer Axles:		0	Cab to Axle (in):	269.9
Type:			Cab to EOF (in):	329.9
Length (ft):		0	Overall Comb. Length (in):	451
Height (ft):		0.0		
Kingpin Inset (in):		0	Special Req.	
Corner Radius (in):		0	United States Registry	
	Restrictions			
Length (ft):		40		
Width (in):		102		
Height (ft):		13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

PACCAR FINANCIAL	Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com .
	PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/19/2017 9:45:48 AM	Complete	Model Number:	Model 567
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q34461153
Prepared by:	Administrator		Version Number:	35.20



Peterbilt of St. Louis P616
2350 Sauget Industrial Parkway

Renegade RV
52216 S.R 15

Sauget, Illinois United States 62206
Phone:
Fax:
Email:

Bristol, Indiana United States 46507
Phone:
Fax:
Contact Email:
Prepared for:

Data	Code	Description	\$ List	Weight
Base Model				
0005671	O	Model 567	170,662	14,860
0091200	O	Other Commodity	0	0
0093170	O	General Freight Truck or tractor used in over-the-road hauling of general freight. Pickup to delivery distance is typically over 100 miles and annual mileage is typically over 60,000 miles per year. Operation is typically on-highway.	0	0
0095040	O	Van	0	0
0098170	O	United States Registry	0	0
Configuration				
0200700	O	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0519180	O	11-5/8in Steel Rails to 444in 11.625 x 3.874 x .375 Dimension, 2,568,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 21.4 cubic inches. Weight: 1.91 lbs/inch pair	999	914
0601700	O	10-3/4 x 3/8in Full Steel Liner For use with 11-5/8in Rail.	2,358	1,531
0611250	O	Heavy-Duty Iron Front Spring Brackets Forward and Rear	289	35
0611790	S	Aluminum Frame Rail Crossmembers Excludes suspension	0	0
0644020	O	EOF Square with Steel Xmbr	30	0
0651220	O	Furnish Mudflap Hangers Only, Omit Flaps (Mudflap/Hanger option is required)	-21	-8
0651800	O	Peterbilt Rear Mudflaps, Stainless Steel Premium Hangers. (Requires two additional inches of overhang for tractors)	193	0

Front Axle & Equipment

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/19/2017 9:45:48 AM	Complete	Model Number:	Model 567
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q34461153
Prepared by:	Administrator		Version Number:	35.20



Data	Code	Description	\$ List	Weight
1012200	O	Meritor MFS20 20,000 lb, 3.74 in Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 20,000 pounds. Axle includes special low-friction bushings, double draw keys and integral thrust bearing and seal design for durability, low maintenance and ease of service. Combination of Meritor Easy Steer king pin bushings, computer-designed and optimized I-beam construction and stiff axle assembly delivering a tight turning radius, superior vehicle control and longer tire life.	1,341	133
1113020	O	Taper Leaf Springs, Shocks 18,000 lb Standard with Heavy Resistance Shocks.	562	119
1243050	O	Power Steering Sheppard HD94 Dual For use with 16,000 to 20,000 lb. axle ratings.	829	0
1250250	O	Power Steering Reservoir Frame Mounted w/Cooler	218	2
1354850	O	PHP10 Iron PreSet PLUS Hubs-Air Disc	51	42
1380070	O	Greasable Front Spring Pins	53	0
1380290	S	Air Disc Front Brakes Complies with reduced stopping distance regulations.	0	0
1380380	S	Tenneco Shocks For Steer Axle	0	0
1380470	O	Meritor Wide Track IPO Standard, Front Axle MFS+ 3.5" Drop / MFS 3.74" Drop. 71in KPI IPO 69in with MFS and MFS+ axles For improved turning radius.	0	5

Rear Axle & Equipment

1526150	O	Meritor MT40-14X 40,000 lb Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	100	90
1616290	S	PHP10 Aluminum PreSet PLUS Hubs	0	0
1632650	S	Long Stroke Parking Brakes, Drive Axle(s)	0	0
1680280	O	Bendix Smart ATC Traction Control	105	2
1680500	O	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	254	0
1680950	O	Stability System Not Selected or Not Available	-100	0
1682710	S	Anti-Lock Braking System (ABS) 6S6M ABS-6. Includes air braking system.	0	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/19/2017 9:45:48 AM	Complete	Model Number:	Model 567
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q34461153
Prepared by:	Administrator		Version Number:	35.20



Data	Code	Description	\$ List	Weight
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687040	O	Air Disc Rear Brakes, Tandem Drive Axle Includes Automatic Slack Adjusters.	2,608	0
1687090	O	Diff Lock Tandem Axles With Speed Interlock. Automatically Disengages Wheel Diff Lock at Speeds Above 25 mph.	1,824	0
1703360	O	Ratio 3.36 Rear Axle	0	0
1821970	O	Peterbilt Low Air Leaf 40,000lb,52in Axle Spacing Light Weight	786	-59
1921040	O	(4) Heavy-Duty Truckmaster Shocks Use with Peterbilt Air Leaf, Low Air Leaf, or Air Trac tandem suspensions.	76	0
1922260	O	Dash Mtd Dump Switch With Indicator Light For suspension	42	2
1922390	O	Heavy-Duty Tracking Rods For use with Peterbilt Air Leaf, Low Air Leaf, Low Low Air leaf, or 40,000 lb Air Trac (standard on 44,000 lb Air Trac).	141	11

Engine & Equipment

2059977	O	X15 565@1950 GOV@2000 1850@1150 Performance Series (2017 Emissions) Includes aluminum flywheel housing. Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life. N21320 N205 120..Standard Maximum Speed Limit [LSL] N21330 N207 0....Expiration Distance N21340 P112 120..Hard Maximum Speed Limit N21350 P001 75...Maximum Accelerator Pedal Vehicle Speed N21370 P059 75...Maximum Cruise Speed N21400 N203 252..Reserve Speed Function Reset Distance N21410 N202 0....Maximum Cycle Distance N21420 N206 10...Maximum Active Distance N21430 N201 0....Reserve Speed Limit Offset N21440 P015 NO...Engine Protection Shutdown N21450 P026 NO...Gear Down Protection N21460 P046 1400.Max PTO Speed N21470 P062 NO...Cruise Control Auto Resume N21480 P068 NO...Auto Engine Brake in Cruise N21500 N209 0....Expiration Distance N21510 P520 YES..Enable Idle Shutdown Park Brake Set N21520 P030 5....Timer Setting N21530 P233 YES..Enable Impending Shutdown Warning N21540 P234 60...Timer For Impending Shutdown Warning	5,760	340
---------	---	--	-------	-----

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/19/2017 9:45:48 AM	Complete	Model Number:	Model 567
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q34461153
Prepared by:	Administrator		Version Number:	35.20



Data	Code	Description	\$ List	Weight
		N21550 P516 35...Engine Load Threshold		
		N21570 P031 NO...Idle Shutdown Manual Override		
		N21590 P230 YES...Enable Hot Ambient Automatic Override		
		N21610 P172 40...Low Ambient Temperature Threshold		
		N21620 P173 60...Intermediate Ambient Temperature Threshold		
		N21630 P171 80...High Ambient Temperature Threshold		
2091310	O	Engine Idle Shutdown Timer Disabled	0	0
2091315	O	Enable EIST Ambient Temp Override	0	0
2091372	O	Eff EIST NA Expiration Miles	0	0
2091640	O	Effective VSL Setting NA	0	0
2140200	O	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins ISL, ISM and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2140410	O	Engine Brake Controls Located on RH Column	0	0
2512100	O	275 Amp Alternator, 40SI Brushless	801	10
2521090	S	Immersion Type Block Heater 110-120V Standard location is center left hand under cab and includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	0	0
2522050	S	PACCAR 12V Starter	0	0
2538050	O	4 PACCAR Premium 12V Dual Purpose Batt 2920 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	243	62
2621000	O	2-Speed Fan Clutch For Frequent Start/Stops	306	0
2723220	O	Naturally Aspirated 18.7 CFM Air Compressor X15 Only	0	0
2812170	O	Intebrake (Furnished on Engine)	0	0
2921130	O	DAVCO 382 Fuel/Water Separator	146	0
2921250	O	Coolant Heat for Fuel Filter	234	0
2921340	O	12V and 120V Heat for Fuel Filter	219	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 587: 1330 sq in, 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 384/386: 1301 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 320: 1242 sq in.	0	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/19/2017 9:45:48 AM	Complete	Model Number:	Model 567
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q34461153
Prepared by:	Administrator		Version Number:	35.20



Data	Code	Description	\$ List	Weight
3291680	S	(1) Air Cleaner Firewall Mounted Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0	0
3365290	O	Exhaust Single RH Horizontal DPF/SCR RH Under Frame (2017).	-544	-187

Transmission & Equipment

4024130	O	Eaton FO18E313A-MHP 13 Speed UltraShift PLUS Multi-Purpose High Performance. Includes oil-to-water cooler. Features two-pedal operation for driver convenience. A Hill Start Aid (HSA) feature is included to prevent roll back or roll forward while launching on grades by employing the trucks foundation brakes. Synthetic lubricant to reduce friction, improve efficiency, and extend component life. Magnetic transmission oil drain plug captures and holds any metal fragments in transmission oil to extend service life. Torque limiting clutch brake. Forward Ratios: 1st-12.29, 2nd-8.51, 11th-1.00, 12th-0.86, 13th-0.73 / Reverse Ratios: R1-15.06, R2-12.85, R3-4.03	8,870	190
4210290	O	1810 HD Driveline, 3 Midship Bearings 4.5in x .180 wall tubing	2,283	355
4216590	O	1710 Driveline Interaxle, For Tandem Rear Axles	-10	0
4252610	O	Column Mounted Shifter RH Side	581	0

Air & Trailer Equipment

4510330	O	Bendix AD-IS EP Air Dryer with Heater And Coalescing Filter; Extended Purge	114	0
4520420	O	Pull Cords All Air Tanks	6	0
4540420	S	Nylon Chassis Hose	0	0
4543340	O	Aluminum Painted Air Tanks All air tanks are aluminum with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	265	-45
4543430	O	Clear Outside Frame of All Air System Components LH BOC	295	0
4543440	O	Clear Outside Frame of All Air System Components RH BOC	295	0
4611930	O	Body Connections 5ft BOC Junction Box contains light and power circuits for Body Connections located 5ft from BOC.	188	6
4611960	O	Hand Valve Plumbed To All Service Brakes	-192	11
4614820	O	Air & Electric Connections in EOF Crossmember	86	-11

Tires & Wheels

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/19/2017 9:45:48 AM	Complete	Model Number:	Model 567
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q34461153
Prepared by:	Administrator		Version Number:	35.20



Data	Code	Description	\$ List	Weight
5069880	O	FF: BR 20ply 315/80R22.5 R249	682	74
5169370	O	RR: BR 14ply 295/75R22.5 M710 ECOPIA Diameter = 40.6 inches; SLR = 18.9 inches	-100	32
5190008	O	Code-rear Tire Qty 08	0	0
5220530	O	FF: Alcoa 89U647 22.5X9.00 Clean Buff Finish Aluminum, Ultra ONE wheels with MagnaForce alloy.	522	-20
5320410	O	RR: Alcoa 885657 22.5X8.25 Clean Buff Finish Aluminum wheel severe service.	2,004	-136
5390008	O	Code-rear Rim Qty 08	0	0
5407640	O	FF: Polish Wheels, Outer Surface, SGL/TDM Steer Polish outer surface of outer wheel. Without chrome wheel nuts.	51	0
5407660	O	RR: Polished Wheels, Outer Surface, Tandem Drive Polish outer surface of outer wheels (4). Without chrome wheel nuts.	204	0

Fuel Tanks

5551100	O	26in Aluminum 70 Gallon Fuel Tank RH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	336	18
5554190	O	26in Aluminum 100 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	369	22
5601070	O	Location RH U/C 70 Gallon	0	0
5602100	O	Location LH U/C 100 Gallon	0	0
5650550	O	Polish (2) Non-Slip Fuel Tank Steps,U/C Tank Only	52	0
5652830	O	Polish All Fuel / Hydraulic Tank Straps Does not apply to Rectangular Def Tank straps.	110	0
5652840	O	Locking Fuel Tank Cap(s)	28	0
5652850	O	Perforated Metal Anti-Siphon Device(s) (Requires Engineering review with Arctic Fox or Split Fuel Tanks)	122	0
5652890	O	DEF Tank Mounted LH BOC Models 210, 220 and 320 mounted LH cab fender.	0	0
5652980	O	Less Than Standard DEF To Fuel Ratio 2:1 Greater than minimum 1:1	0	0
5653000	O	Polished Stainless Steel Cover For DEF Tank	182	0
5655029	O	DEF Tank Medium	104	22

Battery Box & Bumper

6010800	O	Install Batteries On Temp Plywood Support BOC Includes maximum length battery cables allowable per engine manufacture requirements. Recommend three or more batteries for Class 8.	-116	-37
---------	---	--	------	-----

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/19/2017 9:45:48 AM	Complete	Model Number:	Model 567
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q34461153
Prepared by:	Administrator		Version Number:	35.20



Data	Code	Description	\$ List	Weight
6040260	O	Omit RH Under Cab Tool Box	0	0
6113060	O	Aluminum Bumper Deep Taper Stainless Steel Clad Bright Mirror Finish. Two tow pins.	-175	-31
Cab & Equipment				
6515770	O	Vocational 121 BBC Alum Cab and Metton Hood SFFA Stainless steel crown and grille with tilt assist.	3,149	-30
6540160	O	Thermal Insulation Package in Cab Includes thick, closed-cell foam in floor, special mylar-faced foam in walls and roof structure.	19	2
6540660	O	SmartSound Cab Insulation Package Cab acoustic insulation package for day cabs. Includes insulated inside firewall, top side floor damping, absorber treated kick panels, and insulated backwall and roof structure.	398	65
6540740	O	Peterbilt Keyless Entry The Peterbilt key fob functions to lock or unlock the vehicle. With a single click, the driver's door is locked or unlocked and with a double click all doors are locked or unlocked. The third button, depicted by a picture of a lamp, will start the exterior light self-test sequence, helpful when performing the daily pre-trip inspection.	118	2
6810101	U	BOC WALK-THRU CUTOUT IN LOW ROOF DAY CA B N68140 OAR479052	2,550	1
6911740	O	Peterbilt LX Driver Peterbilt LX Air seat, high height backrest, adjustable seat track length, 2 chamber lumbar support, premium suspension with adjustable damping, auto leveling, exit air dump, memory for sitting height, fore-aft isolator with lockout, vinyl bellows over suspension, Requires folding armrests, side and back storage pocket. Standard with fabric/vinyl finish - color coordinated with interior color	205	-12
6921130	O	Peterbilt LX Passenger seat Peterbilt LX Air seat, high height backrest, adjustable seat track length, 2 chamber lumbar support, premium suspension with adjustable damping, auto leveling, exit air dump, memory for sitting height, fore-aft isolator with lockout and vinyl bellows over suspension. Standard with fabric / vinyl - color coordinated with interior color.	625	28
6930580	O	Drivers Armrests - LH & RH Required in Model 587 with Evolution LX seats, optional with Evolution ST and Rolltek Seats.	163	4
6930590	O	Passenger Armrest - LH only Required with Evolution LX seats, optional with Evolution ST Seats.	115	2
6933011	U	Passenger swivel seat N69310 this will have a sleeper rear N69320 opening for the swivel	602	11
6939080	O	Driver Seat Comfort Package Leather Only. Includes ventilation & heating system, adjustable side bolsters in seatback.	1,084	2

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/19/2017 9:45:48 AM	Complete	Model Number:	Model 567
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q34461153
Prepared by:	Administrator		Version Number:	35.20



Data	Code	Description	\$ List	Weight
6939400	S	Air Ride Driver	0	0
6939420	S	High Back Driver	0	0
6939450	O	Leather Driver	320	0
6939500	O	Air Ride Passenger	0	0
6939520	S	High Back Passenger	0	0
6939550	O	Leather Passenger	320	0
7001520	O	Adjustable Steering Column - Tilt/Telescope	500	10
7001630	O	Premium Steering Wheel w Multi Function Premium Multi-functional Leather Wrapped Steering Wheel with Peterbilt logo over horn button. Includes audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.	413	5
7037170	O	Platinum Interior - Sterling Gray Features elegant dual tone dash with tough, scratch resistant materials including soft touch points on top of dash highlighted by horizontal chrome accent, bright bezel gauges. Includes unique technical grained A,B & C instrument panels with teak woodgrain trim and bright accents with contoured doorpads highlighted by a teak woodgrain insert, padded fabric headliner and vinyl wall panels. Superior ergonomics are achieved while maximizing productivity featuring: Peterbilt SmartNav System, pull-out work surface, multiple power ports, header-mounted domelight, power lift driver and passenger windows, LH and RH door mounted map pockets with built-in courtesy lights, driver and passenger dome/reading lights and footwell lighting. Comfort features include automatic temperature HVAC controls, multi-function 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, carpeted floor covering, (3) inside sunvisors, integrated "dead pedal", cup holder and map bin in dash.	4,032	25
7040180	O	Privacy Curtain Around Windshield	254	17
7210540	S	Day Cab Rear Window	0	0
7230060	S	One Piece Curved Windshield	0	0
7230360	S	Power Door Locks AND Power Window Lifts Standard	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7410040	O	Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper or furnished by owner sleeper.	709	8
7514010	O	Peterbilt Aero Rear View Mirror, Motorized Includes top mirror with motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	361	3
7514020	S	Aero Rear View Mirror Housing - Body Color	0	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/19/2017 9:45:48 AM	Complete	Model Number:	Model 567
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q34461153
Prepared by:	Administrator		Version Number:	35.20



Data	Code	Description	\$ List	Weight
7514050	S	Look Down Mirror Over Passenger Door with Black Housing	0	0
7610500	S	Air Horn Mounted Under Cab	0	0
7725730	O	Premium Speaker Package for Cab (4) Speakers with 2 tweeters	540	6
7749490	O	Sirius-XM Satellite Radio Service Provider Option designates XM Satellite Radio - subscription required (800-852-9696).	0	0
7788055	S	SmartLINQ Remote Diagnostics SmartLINQ is Peterbilt's proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesn't require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. SmartLINQ is standard with MX-13 engines and available on the models 587,579,567,389,367 and 365.	0	0
7851040	O	Removable Bugscreen Behind Grille	176	2
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7852020	O	Cab Air Suspension	230	15
7852050	O	Auto Reset Circuit Protection Daycab and Sleeper	18	0
7852080	O	Pull Out Tray/Work Surface Over Glove Box	176	3
7900090	O	Triangle Reflector Kit Shipped Loose	18	13
7900310	O	Fire Extinguisher; Mounted Outboard Driver Seat Hazmat approval UL listed/rated ABC.	89	8
7900405	O	Anti-Theft System Available on PACCAR MX and Cummins ISX-12 and ISX-15 Engines. System disables the cranking of the engine until a unique passcode is entered, via the menu control switch, into the pop-up menu. The unique passcode is set up initially by the Dealer Service Department.	0	0
7901130	O	Backup Alarm (107dB)	121	3
8011140	O	Engine Oil Temperature Located in SmartNav display	0	0
8011150	O	Main Transmission Oil Temperature Located in SmartNav display	25	0
8011160	O	Drive Axle #1 Front Oil Temperature Located in SmartNav display	104	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/19/2017 9:45:48 AM	Complete	Model Number:	Model 567
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q34461153
Prepared by:	Administrator		Version Number:	35.20



Data	Code	Description	\$ List	Weight
8011170	O	Drive Axle #2 Rear Oil Temperature Located in SmartNav display	119	0
8012240	O	Guard(s) For Rear Axle Heat Gauge	77	2
8021410	O	General Air Pressure 1 Gauge Located in SmartNav display	145	0
8021550	O	Air Suspension Pressure 1 Gauge Located in SmartNav display	102	0
8021560	O	Air Filter Restriction Pressure Located in SmartNav display	0	0
8022500	O	Fuel Filter Restriction / Pressure Gauge Located in SmartNav display	110	0
8070040	O	Fill Panels With Additional Electric Switches Without wiring	522	2
8070110	O	(5) Additional Dash Switches With Wiring Located on dash panel C. Availability subject to dash space. Includes 4 in. 14 gauge wire with butt splice at rear of each additional switch.	268	2
8070120	O	Manifold Pressure, Boost Located in SmartNav display	0	0
8070130	O	Tractor Brake Application Located in SmartNav display	68	0
8070170	O	DPF Status Located in SmartNav display	0	0
8070180	O	Fuel Economy Located in SmartNav display	0	0
8070190	O	Percent Torque Located in SmartNav display	0	0
8071340	O	Bright Bezel Gauges	100	0
8071890	S	Main Instrument Panel Includes Driver Information Display and Instrument Package With Speedometer, Tachometer, Fuel Level Gauge, Engine Oil Pressure, Engine Coolant Temperature, (2) Air Pressure, DEF Level Gauge. With Gas Engines, DEF Level Gauge will be replaced with Brake Application Gauge.	0	0
8110070	O	Headlights Projector Module Pod Fender mounted turn signals. Projector Module Low Beam, Complex Reflector High Beam. Pod Mounted.	0	0
8120990	S	(5) Marker Lights, Aero LED On roof, visor, or fairing.	0	0
8131560	O	(2) Peterbilt Fog Lights Recessed in bumper	203	6
8133110	O	Switch and Wiring F/O Auxiliary Light Under cab/sleeper (15 amp max.). Includes switch on the dash which will power metri-pack sealed connections at the RH/LH side of cab at the base of the firewall.	35	2

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/19/2017 9:45:48 AM	Complete	Model Number:	Model 567
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q34461153
Prepared by:	Administrator		Version Number:	35.20



Data	Code	Description	\$ List	Weight
8133960	S	Daytime Running Lights (Required on Canadian units)	0	0
8140080	O	LED Stop/Turn/Tail/Backup Bracket mounted LH/RH EOF	46	2
8140650	O	Peterbilt Signature Door Light Turn Signal	0	0
8141010	O	Wiring For Additional Set Turn Signals Mounted under corners cab or sleeper	80	5
8153050	O	(1) F/O Load Light, Switch & (2) 10 Ft Wire Coils Under Cab/Sleeper	98	3

Paint

8500710	O	Standard Paint Color Selection	-200	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE - STAND N85400 HOOD TOP L0006EY WHITE - STAND N85500 CAB ROOF L0006EY WHITE - STAND N85200 FRAME N0001EA BLACK N85300 FENDER L0006EY WHITE - STAND	0	0

Miscellaneous

9409002	O	Day Cab / Platinum Interior (DP)	0	0
9409800	O	2017 EPA Emissions Engine Warranty Only	0	0
9409960	O	Presentation Created Using Featured Spec For Model	0	0

Total Adjusted Price (W/O Freight & Warranty & Surcharges)	\$226,928
Freight Charge	\$2,225
Options Not Subject to Discount	\$0
Surcharges Not subject to Discount	\$0
Total Weight	18571

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/19/2017 9:45:48 AM	Complete	Model Number:	Model 567
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q34461153
Prepared by:	Administrator		Version Number:	35.20